

PRODUCT DESCRIPTION

Cleans, restores and brings back the natural color of teak and other hardwoods. Gentle formula, does not bleach or damage surrounding fiberglass, wood, metals and painted surfaces. Contains Tenside cleaners, which are excellent at removing oil and dirt.

- * Restores the natural color of teak
- * For use on any interior or exterior hardwood.
- * For decks, teak details and finishing.
- * Does not damage fiberglass, varnish, paintwork or metals.

PRODUCT INFORMATION

Colour	YMA015-Clear
Specific Gravity	0.99
Unit Size	16.9 fl oz/500 ml

DRYING/OVERCOATING INFORMATION

Drying

Overcoating Substrate Temperature

Overcoated By	Min	Max	Min	Max	Min	Max	Min	Max
---------------	-----	-----	-----	-----	-----	-----	-----	-----

APPLICATION AND USE

Preparation	Wet out the teak thoroughly with fresh or salt water.
Method	Apply Interlux Premium Teak Restorer generously and leave for 10-15 minutes. Scrub the surface across the grain. Repeat if necessary. Rinse with fresh water. For protection of the restored wood, treat with Interlux Teak Oil.
Hints	Mixing Shake well before use.
Some Important Points	Product temperature should be minimum 5°C/40°F and maximum 35°C/95°F. Substrate temperature should be minimum 5°C/40°F and maximum 35°C/95°F. Ambient temperature should be minimum 5°C/40°F and maximum 35°C/95°F. Keep from freezing.
Compatibility/Substrates	Suitable for use on teak and other hardwoods.
Recommended DFT	
Application Methods	Brush , cloth

TRANSPORTATION, STORAGE AND SAFETY INFORMATION

Storage	<p>GENERAL INFORMATION: Exposure to air and extremes of temperature should be avoided. For the full shelf life of Premium Teak Restorer to be realised ensure that between use the container is firmly closed and the temperature is between 5°C/40°F and 35°C/95°F. Keep out of direct sunlight.</p> <p>TRANSPORTATION: Premium Teak Restorer should be kept in securely closed containers during transport and storage.</p>
Safety	GENERAL: Read the label safety section for Health and Safety Information, also available from our

Technical Help Line.

DISPOSAL: Do not discard tins or pour paint into water courses, use the facilities provided. It is best to allow paints to harden before disposal.

IMPORTANT NOTES

The information given in this sheet is not intended to be exhaustive. Any person using the product without first making further written enquiries as to the suitability of the product for the intended purpose does so at their own risk and we can accept no responsibility for the performance of the product or for any loss or damage (other than death or personal or injury resulting from negligence) arising out of such use. The information contained in this sheet is liable to modification from time to time in the light of experience and our policy of continuous product development.

X and International are registered trademarks of Akzo Nobel.

Regional Addresses

Head Office

International Paint Ltd
P O Box 20980
Oriol House
16 Connaught Place
London W2 2ZB
United Kingdom
tel: +44 (0) 171 479 6000
fax: +44 (0) 171 479 6500

European Region

International Paint Ltd
Stoneygate Lane
Felling, Gateshead
Tyne & Wear NE10 0JY
United Kingdom
tel: +44 (0) 191 469 6111
fax: +44 (0) 191 438 3977

Asia Region

International Paint Singapore
(Pte) Ltd
449 Tagore Industrial Avenue
01-03 Hong Joo Industrial
Building
Singapore 787820
tel: +65 6453 1981
fax: +65 6453 1778

Australasia Region

International Paint
115 Hyde Road
Yeronga, Brisbane
Queensland 4104
Australia
tel: +61 (0) 7 3892 8866
fax: +61 (0) 7 3892 4287

North America Region

International Paint LLC
2270 Morris Avenue
Union
New Jersey 07083
USA
tel: +1 (0) 908 686 1300
fax: +1 (0) 908 686 8545

South America Region

International Paint
Rod Rap tavares, KM 18.5
Predio Administrativo 11
Butanta CEP 05577-300
Sao Paulo, Brazil
tel: +55 (0) 11 3789 2000
fax: +55 (0) 11 3789 2200



Ref: 05000466
Issue Date: 11-Aug-2005
Supersedes: 8-Jul-2004